

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

U.S. APPLICATION NO. (If known see 37 C.F.R. 1.5)

INTERNATIONAL APPLICATION NO.

INTERNATIONAL FILING DATE

(EARLIEST) PRIORITY DATE CLAIMED

PCT/JP00/01271

03 March 2000

03 March 1999

TITLE OF INVENTION

**TRANSMITTING APPARATUS, RECEIVING APPARATUS, TRANSMITTING
AND RECEIVING SYSTEM, TRANSMITTING METHOD, AND RECEIVING
METHOD**

APPLICANTS FOR DO/EO/US

**Fumihiko NISHIO, Yoshihisa GONNO, Kazuo HARAOKA, Kazuhiko
TAKABAYASHI and Yasuaki YAMAGISHI**

Applicants herewith submit to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)), including 8 sheets of formal drawings and a copy of the International Search Report.
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventors (35 U.S.C. 371(c)(4)).
10. ☐ The annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern other document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☒ Other items or information:

PCT/ISA/210, PCT/RO/101

References for IDS

EXPRESS MAIL

Mailing Label Number: **EL 5850298761US**

Date of Deposit: **November 2, 2000**

I hereby certify that this paper or fee is being deposited with the United States Postal Service

"Express Mail Post Office to Addressee" Service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents and Trademarks, Box PCT Washington, DC 20231.

(Typed or printed name of person mailing paper or fee)

(Signature of person mailing paper or fee)

17. ☒ The following fees are submitted:

(CALCULATIONS /PTO USE ONLY)

Basic National Fee (37 CFR 1.492(a)(1)-(5)):

Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO... \$ 1000.00

International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO... \$ 860.00

International preliminary examination fee paid to USPTO (37 CFR 1.482) Not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO (37 CFR 1.445(a)(2))... \$ 710.00

International preliminary examination fee paid to USPTO (37 CFR 1.482) But all claims did not satisfy provisions of PCT Article 33(1)-(4)... \$ 690.00

International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4)... \$ 100.00

ENTER APPROPRIATE BASIC FEE AMOUNT =

(\$ 860.00)

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(e)).

2. Claims /	Number Filed	/Number Extra	/Rate	(
Total Claims	/ 9 - 20 =	/ 0	X \$18.00	(\$ 0.00
Independent Claims	/ 7 - 3 =	/ 4	/X \$80.00	(\$ 320.00
Multiple dependent claim(s) (if applicable)			/+ \$260.00	(\$

TOTAL OF ABOVE CALCULATIONS =

(\$ 1,180.00)

Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity (statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28).

SUBTOTAL =

(\$ 1,180.00)

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(f)).+

TOTAL NATIONAL FEE =

(\$ 1,180.00)

Fee for recording the enclosed assignments (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) \$40.00 per property +

TOTAL FEES ENCLOSED =

(\$ 1,220.00)

(Amount to be: refunded)	/ \$
(charged)	/ \$

- a. ☒ Our checks in the amount of \$1,220.00 to cover the above fees is enclosed.
b. ☐ Please charge my Deposit Account No. 50-0320 in the amount of \$_____ to cover the above fees.

A duplicate copy of this sheet is enclosed.

- c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 50-0320. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

WILLIAM S. FROMMER
FROMMER LAWRENCE & HAUG LLP
745 FIFTH AVENUE
NEW YORK, NEW YORK 10151

Dated: November 2, 2000

William S. Frommer
SIGNATURE
WILLIAM S. FROMMER
NAME

25,506
REGISTRATION NUMBER

DESCRIPTION

~~Transmitting Apparatus, Receiving Apparatus,
Transmitting and Receiving System, Transmitting Method,
and Receiving Method~~

5 Technical Field

The present invention relates to a transmitting apparatus, a receiving apparatus, a transmitting and receiving system, a transmitting method, and a receiving method for use with a digital broadcasting system that is structured on for example the Internet and that delivers contents data.

Related Art

Although many techniques for delivering contents data have been proposed, document data written in HTML (Hyper Text Mark-up Language) is delivered on the Internet (hereinafter, these document data is referred to as HTML document). In the HTML, hyper links are represented using URIs (Uniform Resource Identifier) so as to correlate a plurality of HTML documents.

In recent years, in the field of broadcasts, a digital broadcasting system that is structured on the Internet and that delivers HTML documents therethrough has been studied. The digital broadcasting system uses digital televisions and so forth as receiving terminal units. In a conventional digital broadcast that corresponds to DVB (Digital Video Broadcasting)

standard or the like, identifiers of ID values such as event_id, service_id, and component_tag are assigned to video/audio streams. In such a digital broadcasting system, URIs are added to individual resources of delivered data (video/audio stream, digital data of a digital broadcast, and so forth). Each of delivered HTML documents that are broadcast can be hyper-linked.

As a method for adding a URI to broadcast data while keeping the compatibility with the conventional digital broadcasting system, a descriptor that contains a URI can be used. In this method, when a link is selected with a URI of an HTML document by a receiver, a relevant URI is searched from a descriptor area of a received MPEG-2 section table or the like and a resource that contains the URI is accessed (displayed). In this case, since a URI is written as text data, the URI searching process includes a text pattern matching process. Thus, on the receiver side, the load imposed for this process is heavier than that for the process for simply comparing ID values.

Therefore, an object of the present invention is to provide a transmitting apparatus, a receiving apparatus, a transmitting and receiving system, a transmitting method, and a receiving method that allow the load imposed to a receiving apparatus and so forth to be alleviated for a contents data identifying process for matching URIs.

Disclosure of the Invention

The invention of claim 1 is a receiving apparatus for receiving contents data, comprising:

5 a receiving means for receiving data that is transmitted;

a first identifier converting means for converting an indefinite length identifier contained in the data into a fixed length identifier;

10 a reception information storing means for storing contents data contained in the data, the indefinite length identifier, and the fixed length identifier;

15 an inputting means for inputting a user's request for contents data;

a second identifier converting means for converting an indefinite length identifier added to the contents data corresponding to the user's request into a fixed length identifier; and

20 a contents data identifying means for comparing the fixed length identifier stored in the reception information storing means with the fixed length identifier that is output from the second identifier converting means, generating the compared result of the fixed length identifiers, and identifying
25 the contents data corresponding to the user's request using the generated compared result of the fixed length identifiers.

The invention of claim 3 is a transmitting and receiving system, comprising:

a transmitting apparatus having:

a transmission data storing means for storing contents data,

an identifier adding means for adding an indefinite length identifier to the contents data, and

a transmitting means for transmitting the contents data and the indefinite length identifier; and

a receiving apparatus having:

a receiving means for receiving data that is transmitted,

a first identifier converting means for converting an indefinite length identifier contained in the data into a fixed length identifier,

a reception information storing means for storing contents data contained in the data, the indefinite length identifier, and the fixed length identifier,

an inputting means for inputting a user's request for contents data,

a second identifier converting means for converting an indefinite length identifier added to the contents data corresponding to the user's request into a fixed length identifier, and

a contents data identifying means for comparing the fixed length identifier stored in the

reception information storing means with the fixed length identifier that is output from the second identifier converting means, generating the compared result of the fixed length identifiers, and identifying the contents data corresponding to the user's request using the generated compared result of the fixed length identifiers.

The invention of claim 4 is a transmitting apparatus for transmitting contents data, comprising:

a transmission data storing means for storing contents data;

an identifier adding means for adding an indefinite length identifier to the contents data;

an identifier converting means for converting the indefinite length identifier into a fixed length identifier; and

a transmitting means for transmitting the contents data, the indefinite length identifier, and the fixed length identifier.

The invention of claim 5 is a receiving apparatus for receiving contents data, comprising:

a receiving means for receiving data that is transmitted;

a reception information storing means for storing contents data contained in the data and a fixed length identifier;

an inputting means for inputting a user's

request for contents data;

an identifier converting means for converting
an indefinite length identifier added to the contents
data corresponding to the user's request into a fixed
length identifier; and

a contents data identifying means for
comparing the fixed length identifier stored in the
reception information storing means with the fixed
length identifier that is output from the identifier
converting means, generating the compared result of the
fixed length identifiers, and identifying the contents
data corresponding to the user's request using the
generated compared result of the fixed length
identifiers.

The invention of claim 7 is a transmitting
and receiving system, comprising:

a transmitting apparatus having:

a transmission data storing means for storing
contents data,

an identifier adding means for adding an
indefinite length identifier to the contents data,

an identifier converting means for converting
the indefinite length identifier into a fixed length
identifier;

a transmitting means for transmitting the
contents data, the indefinite length identifier, and
the fixed length identifier; and

a receiving apparatus having:

a receiving means for receiving data that is transmitted,

a reception information storing means for
5 storing contents data and an indefinite length
identifier contained in the data and the fixed length
identifier,

an inputting means for inputting a user's
request for contents data,

10 an identifier converting means for converting
an indefinite length identifier added to the contents
data corresponding to the user's request into a fixed
length identifier, and

a contents data identifying means for
15 comparing the fixed length identifier stored in the
reception information storing means with the fixed
length identifier that is output from the identifier
converting means, generating the compared result of the
fixed length identifiers, and identifying the contents
20 data corresponding to the user's request using the
generated compared result of the fixed length
identifiers.

The invention of claim 8 is a transmitting
method for transmitting contents data, comprising the
25 steps of:

storing contents data;

adding an indefinite length identifier to the

contents data;

converting the indefinite length identifier
into a fixed length identifier; and

transmitting the contents data, the
5 indefinite length identifier, and the fixed length
identifier.

The invention of claim 9 is a receiving
method for receiving contents data, comprising the
steps of:

10 receiving data that is transmitted;
storing contents data, an indefinite length
identifier, and a fixed length identifier contained in
the data;

15 converting the indefinite length identifier
contained in the data into a fixed length identifier;
inputting a user's request for contents data;
converting an indefinite length identifier
added to the contents data corresponding to the user's
request into a fixed length identifier;

20 comparing the result of the first identifier
converting step with the result of the second
identifier converting step; and

25 identifying the contents data corresponding
to the user's request using the result of the fixed
length identifier comparing step.

According to the present invention set forth
in claims 1 and 3, an indefinite length identifier such

as a URI added to contents data included in data received by the receiving apparatus is converted into a fixed length identifier using the Hash function or the like. In addition, an indefinite length identifier added to contents data corresponding to a user's request is converted into a fixed length identifier using the Hash function or the like. These identifiers are compared. Corresponding to the compared result, the contents data corresponding to the user's request is identified.

According to the present invention set forth in claims 4, 5, 7, and 9, after an indefinite length identifier is added to contents data, a fixed length identifier into which an indefinite length identifier has been converted using the Hash function or the like is further added to the contents data. The resultant contents data is transmitted by a transmitting apparatus. The fixed length identifier is compared with a fixed length identifier into which an indefinite length identifier added to contents data corresponding to a user's request has been converted using the Hash function or the like by a receiving apparatus. Corresponding to the compared result, the contents data corresponding to the user's request is identified.

Brief Description of Drawings

Fig. 1 is a schematic diagram showing an example of the structure of a digital broadcasting

system according to an embodiment of the present invention;

Fig. 2 is a block diagram showing an example of a structure of a contents data transmitting portion of a broadcasting station according to the embodiment of the present invention;

Fig. 3 is a block diagram showing an example of the structure of a receiving terminal according to the embodiment of the present invention;

Fig. 4 is a schematic diagram showing an example of a descriptor for adding a URI according to the embodiment of the present invention;

Fig. 5 is a schematic diagram showing an example of the data structure of an EIT;

Fig. 6 is a schematic diagram showing an example of a script for adding a URI according to the embodiment of the present invention;

Fig. 7 is a flow chart for explaining a URI converting process according to the embodiment of the present invention;

Fig. 8 is a flow chart for explaining a URI comparing process according to the embodiment of the present invention;

Fig. 9 is a block diagram showing an example of the structure according to a contents data transmitting portion of the broadcasting station according to another embodiment of the present

invention;

Fig. 10 is a block diagram showing an example of the structure of a receiving terminal unit according to the other embodiment of the present invention;

5 Fig. 11 is a schematic diagram showing an example of a descriptor used for adding a URI according to the other embodiment of the present invention; and

Fig. 12 is a schematic diagram showing an example of a notation for adding a URI according to the other embodiment of the present invention.

Best Modes for Carrying out the Invention

10 Fig. 1 shows an example of the structure of a digital broadcasting system according to an embodiment of the present invention. Referring to Fig. 1, information providers 101₁, 101₂, ... each have a server, a HDD (Hard Disk Drive), and so forth. Each of
15 the information providers 101₁, 101₂, ... stores and/or transmits contents data supplied using a database composed of such structural portions. Examples of
20 contents data are WWW pages and video/audio streams. The information providers 101₁, 101₂, ... are connected to a broadcasting station 102 through a bidirectional network 105. The information providers 101₁, 101₂, ... can transmit contents data to the broadcasting station
25 102 through the bidirectional network 105.

In addition, the information providers 101₁, 101₂, ... are connected to receiving terminal units

103₁, 103₂, ... through the bidirectional network 105.
The information providers 101₁, 101₂, ... can transmit
contents data to the receiving terminal units 103₁,
103₂, ... through the bidirectional network 105.

5 The broadcasting station 102 has a server, a
HDD, and so forth. The broadcasting station 102 stores
and/or supply contents data that is transmitted to a
broadcasting network 104 to a database composed of the
structural portions thereof. Examples of the contents
10 data are broadcast programs. The broadcasting station
102 is connected to the receiving terminal units 103₁,
103₂, ... through the broadcasting network 104. Thus,
the broadcasting station 102 can supply the contents
data and a URI that identifies thereof to the receiving
15 terminal units 103₁, 103₂, ... through the broadcasting
network 104. In addition, the broadcasting station 102
can receive contents data from the information
providers 101₁, 101₂, ... through the bidirectional
network 105 or a dedicated line and supply the received
20 contents data to the receiving terminal units 103₁,
103₂, ... through the broadcasting network 104.

Each of the receiving terminal units 103₁,
103₂, ... designates desired contents data with a URI.
Examples of contents data designated with a URI are a
25 program that is transmitted (broadcast) through the
broadcasting network 104 on real time basis, a program
that is pre-transmitted through the broadcasting

network 104 and stored to the receiving terminal units 103₁, 103₂, ..., and data that is accessed through the bidirectional network 105 on demand basis. Although the present invention can be applied to a contents data
5 identifying process that is accessed through any route, in the following description, it is assumed that contents data that is transmitted through the broadcasting network 104 is identified.

Fig. 2 shows an example of the structure of a
10 contents data transmitting portion of the broadcasting station 102. Referring to Fig. 2, a transmission information storing portion 201 stores contents data supplied to the receiving terminal units 103₁, 103₂, ... In addition, the transmission information storing
15 portion 201 may temporarily store contents data supplied by the information providers 101₁, 101₂, ... The transmission information storing portion 201 may be a HDD or the like. Data stored in the transmission information storing portion 201 is supplied to a URI
20 adding portion 202 at a predetermined timing. The URI adding portion 202 adds a URI as an identifier to each resource of the supplied information, encodes URI information, and supplies the encoded URI information to a transmitting portion 203. The transmitting
25 portion 203 transmits the data supplied from the URI adding portion 202 to the broadcasting network 104 or the like.

Fig. 3 shows an example of the structure of the receiving terminal unit 103₁. Referring to Fig. 3, a receiving portion 301 receives data transmitted through the broadcasting network 104 or the like and supplies the reception data to a URI converting portion 302. The URI converting portion 302 performs a process for converting URI information contained in the supplied data into a Hash function value and obtains a fixed length identifier (this identifier is referred to as Hash function value). The fixed length hash function value is supplied and stored to a reception information storing portion 303 along with data received by the receiving portion 301.

The Hash function is a conversion of which two different inputs that become the same output values cannot be found due to necessity of a huge calculation amount. In other words, an indefinite length URI is converted into a fixed length hash function value whose length is shorter than the length of the URI.

On the other hand, the user of the receiving terminal unit 103₁ inputs a URI added to desired contents data through a URI input portion 307. The URI that is input by the user is supplied to a URI converting portion 305. The URI converting portion 305 converts the input URI into a fixed length hash function value as an identifier. An output of the URI converting portion 305 is supplied to a URI comparing

portion 306. The URI comparing portion 306 appropriately reads the Hash function value stored in the reception information storing portion 303 and compares it with the Hash function value supplied from the URI converting portion 305.

The comparing process for comparing fixed length Hash functions values can be performed by the URI comparing portion 306 easier and quickly than the comparing process for comparing indefinite length URIs. However, because of the characteristic of the Hash function, there is a small probability of which different URIs may be converted into the same Hash function value. Thus, even if Hash function values match each other, a process for determining whether or not URIs match each other is performed.

As the compared result, when the Hash function value stored in the reception information storing portion 303 matches the Hash function value supplied from the URI converting portion 305, the following process is performed.

In other words, indefinite length URIs corresponding to Hash function values that match as the determined result (namely, an infinite length URI that is stored in the reception information storing portion 303 and a URI that is input through the URI converting portion 305) are compared. As the compared result, when the two indefinite length URIs match each other,

it can be determined that the contents data to which the indefinite length URI is added is contents data that the user desires. The identified data is supplied from the URI comparing portion 306 to a displaying portion 307 of a digital television receiver or the like. With the displaying portion 307, the user can see and listen to desired information. The structure of the receiving terminal unit 103₁ may be the same as the structure of the receiving terminal unit 103₂.

Fig. 4 shows an example of a descriptor used in a conventional digital broadcast. The descriptor is used for adding a URI. In this example, the descriptor contains a descriptor tag, a descriptor length, and N characters (each is composed of eight bits). On the other hand, in SI (Service Information) corresponding to DVB or the like, an EIT (Event Information Table) is used. The EIT contains information of for example a program title and broadcast time data added to contents data. Fig. 5 shows an example of the data structure of the EIT. Information about each program is represented in a frame 1201. The frame 1201 has event_id 1203 that identifies each program and a descriptor area 1202. Using this descriptive format, with reference to a script in the descriptor shown in Fig. 4, a URI is correlated with event_id.

Next, the URI adding process performed by the URI adding portion 202 (refer to Fig. 2) will be

described. Fig. 6 shows an example of a script for adding a URI. In this example, a URI "lid://www.abc.com/abc_news/night" is added to a program identified by event_id = 100, namely, ABC news that starts at 21:00 and whose duration is 60 minutes. Thus, a HTML document transmitted as a data broadcast contains an URI "lid://www.abc.com/abc_news/ night". When the user selects it, a channel tuning operation for the program or a timer recoding operation thereof can be performed.

Next, with reference to a flow chart shown in Fig. 7, the URI converting process performed by the URI converting portion 302 (refer to Fig. 3) will be described. A URI descriptor is extracted from received data (at step S701). With a URI character string contained in the URI descriptor, a Hash function value corresponding to for example MD 5 (Message Digest 5) is calculated (at step S702). As the result at step S702, an indefinite length character string uri is converted into a Hash function value (namely, a fixed length character string) h(uri). The hash function value h(uri) is added to contents data. The resultant contents data is stored to the reception information storing portion 303 (at step S703).

Next, with reference to a flow chart shown in Fig. 8, the URI comparing process performed by the URI comparing portion 306 (refer to Fig. 3) will be described. A Hash function value corresponding to MD 5

or the like is calculated with an input character string of a URI character string uri_1 that is input by the user through the URI input portion 304 (refer to Fig. 3). Thus, a Hash function value $h(uri_1)$ is obtained (at step S801). The Hash function value $h(uri_1)$ is compared with the Hash function value $h(uri_i)$ calculated and stored (refer to Fig. 7) (at step S802). As the determined result at step S802, when the Hash function value $h(uri_1)$ matches the Hash function value $h(uri_i)$, the flow advances to step S803. Otherwise, the flow advances to step S805.

At step S803, indefinite length URI character strings that have not been converted into fixed length Hash function values (namely, uri_1 and uri_i) are compared. Because of the characteristic of the Hash function, there is a probability of which Hash function values corresponding to different input URI character strings match each other. Thus, at step S803, it is determined whether uri_1 matches uri_i. As the determined result at step S803, when uri_1 matches uri_i, the flow advances to step S804. Otherwise, the flow advances to step S805. At step S804, a process for displaying contents data to which uri_i that matches uri_1 is added on the displaying portion 307 or the like is performed. At step S805, the value of i is changed. Thereafter, the flow advances to step S802.

In the above-described processes, indefinite

length URI character strings are converted into fixed length identifiers using the Hash function or the like. With the fixed length identifiers, a comparing process is performed. Only when a match is detected, with the indefinite length URIs corresponding to the fixed length identifiers, a comparing process is performed. Thus, the frequency of which the process for comparing indefinite length URIs can be decreased. Consequently, the process for comparing URIs can be effectively performed at high speed. In addition, the load imposed to the receiving terminal units 103₁, 103₂, ... can be alleviated.

In the above-described embodiment, the process for converting URI character strings into Hash function values is performed by the receiving terminal units 103₁, 103₂, ... Alternatively, such a process can be performed on the transmitter side. This case will be described as another embodiment of the present invention. The structure of a transmitting and receiving system according to the other embodiment of the present invention may be the same as that according to the above-described embodiment of the present invention. Next, with reference to Fig. 9, a broadcasting station 1102 according to the other embodiment of the present invention will be described.

In Fig. 9, as a transmission information storing portion 1201 and a URI adding portion 1202, the

transmission information storing portion 201 and the
URI adding portion 202 shown in Fig. 2 can be used. A
URI converting portion 1204 is disposed downstream of
the URI adding portion 202. The URI converting portion
5 1204 performs a process for converting an indefinite
length URI character string added to contents data by
the URI adding portion 1202 into a fixed length
identifier using the Hash function or the like. The
URI converting portion 1204 adds the fixed length
10 character string to an output of the URI adding portion
202. The generated data is supplied to a transmitting
portion 1203. The transmitting portion 1203 performs a
process for transmitting the supplied data to the
broadcasting network 104 or the like.

15 Next, with reference to Fig. 10, a receiving
terminal unit 1103, according to the other embodiment
of the present invention will be described. In Fig.
10, a receiving portion 1301 receives data transmitted
through the broadcasting network 104 or the like. The
20 data received by the receiving portion 1301 is data of
which an indefinite length URI, a fixed length
identifier that is generated using the Hash function or
the like, and so forth are added to contents data. The
data received by the receiving portion 1301 is supplied
25 to a reception information storing portion 1303. As
the reception information storing portion 1303, a URI
input portion 1307, a URI converting portion 1305, a

URI comparing portion 1306, and a URI input portion 1307, the reception information storing portion 303, the URI input portion 307, the URI converting portion 305, the URI comparing portion 306, and the displaying 307 shown in Fig. 3 can be used, respectively.

Fig. 11 shows an example of a descriptor for adding a URI according to the other embodiment of the present invention. As with the example of the descriptor according to the above-described embodiment described with reference to Fig. 4, the descriptor shown in Fig. 11 contains a descriptor tag, a descriptor length, N characters, and a URI Hash function value URI_hash_value.

Fig. 12 shows an example of a script for storing an URI in an EIT descriptor area. In this example, as with an example of a script according to the above-described embodiment shown in Fig. 6, a URI "lid://www.abc.com/abc_news/night" is added to a program identified by event_id = 100, namely, ABC news that starts at 21:00 and whose duration is 60 minutes. However, in this example, a Hash function value b2allafc568b6ddf62badef691cf0b1ed corresponding to the Hash function MD 5 is also added.

According to the present invention, an indefinite length identifier such as a URI added to contents data included in data received by the receiving apparatus is converted into a fixed length

identifier using the Hash function or the like. In addition, an indefinite length identifier added to contents data corresponding to a user's request is converted into a fixed length identifier using the Hash function or the like. These identifiers are compared. Corresponding to the compared result, the contents data corresponding to the user's request is identified.

In addition, according to the present invention, after an indefinite length identifier is added to contents data, a fixed length identifier into which an indefinite length identifier has been converted using the Hash function or the like is further added to the contents data. The resultant contents data is transmitted by a transmitting apparatus. The fixed length identifier is compared with a fixed length identifier into which an indefinite length identifier added to contents data corresponding to a user's request has been converted using the Hash function or the like by a receiving apparatus. Corresponding to the compared result, the contents data corresponding to the user's request is identified.

In these processes, fixed length identifiers are effectively compared at high speed. Only when a match is detected, indefinite length identifiers are compared.

Thus, in the process for identifying contents data, the frequency of which the comparing process that

is slow and ineffective can be suppressed. As a result, the load imposed to the receiving apparatus can be alleviated. Thus, the process for receiving contents data can be performed effectively at high speed.

It should be understood by those skilled in the art that the foregoing and various other changes, omissions, and additions in the form and detail thereof may be made therein without departing from the spirit and scope of the present invention.

CLAIMS

1. A receiving apparatus for receiving contents data, comprising:

receiving means for receiving data that is
5 transmitted;

first identifier converting means for
converting an indefinite length identifier contained in
the data into a fixed length identifier;

reception information storing means for
10 storing contents data contained in the data, the
indefinite length identifier, and the fixed length
identifier;

inputting means for inputting a user's
request for contents data;

15 second identifier converting means for
converting an indefinite length identifier added to the
contents data corresponding to the user's request into
a fixed length identifier; and

20 contents data identifying means for comparing
the fixed length identifier stored in said reception
information storing means with the fixed length
identifier that is output from said second identifier
converting means, generating the compared result of the
fixed length identifiers, and identifying the contents
25 data corresponding to the user's request using the
generated compared result of the fixed length
identifiers.

2. The receiving apparatus as set forth in claim 1,

wherein when said contents data identifying means has determined that the fixed length identifier stored in said reception information storing means matches the fixed length identifier that is output from said second identifier converting means as the compared result of the fixed length identifiers, said contents data identifying means compares the indefinite length identifier corresponding to the fixed length identifier stored in said reception information storing means with the indefinite length identifier corresponding to the fixed length identifier that is output from said second identifier converting means and generates the compared result of the indefinite length identifiers, and

wherein when said contents data identifying means has determined that the indefinite length identifier corresponding to the fixed length identifier stored in said reception information storing means matches the indefinite length identifier corresponding to the fixed length identifier stored in said reception information storing means with the indefinite length identifier corresponding to the fixed length identifier that is output from said second identifier converting means as the determined result of the indefinite length identifiers, said contents data identifying means determines that the contents data identified by the

indefinite length identifier is the contents data corresponds to the user's request.

3. A transmitting and receiving system, comprising:

5 a transmitting apparatus having:

transmission data storing means for storing contents data,

10 identifier adding means for adding an indefinite length identifier to the contents data, and transmitting means for transmitting the contents data and the indefinite length identifier; and

a receiving apparatus having:

receiving means for receiving data that is transmitted,

15 first identifier converting means for converting an indefinite length identifier contained in the data into a fixed length identifier,

20 reception information storing means for storing contents data contained in the data, the indefinite length identifier, and the fixed length identifier,

inputting means for inputting a user's request for contents data,

25 second identifier converting means for converting an indefinite length identifier added to the contents data corresponding to the user's request into a fixed length identifier, and

contents data identifying means for comparing
the fixed length identifier stored in said reception
information storing means with the fixed length
identifier that is output from said second identifier
5 converting means, generating the compared result of the
fixed length identifiers, and identifying the contents
data corresponding to the user's request using the
generated compared result of the fixed length
identifiers.

10 4. A transmitting apparatus for transmitting
contents data, comprising:
transmission data storing means for storing
contents data;

15 identifier adding means for adding an
indefinite length identifier to the contents data;
identifier converting means for converting
the indefinite length identifier into a fixed length
identifier; and

20 transmitting means for transmitting the
contents data, the indefinite length identifier, and
the fixed length identifier.

5. A receiving apparatus for receiving contents
data, comprising:

25 receiving means for receiving data that is
transmitted;

reception information storing means for
storing contents data contained in the data and a fixed

length identifier;

inputting means for inputting a user's request for contents data;

5 identifier converting means for converting an indefinite length identifier added to the contents data corresponding to the user's request into a fixed length identifier; and

10 contents data identifying means for comparing the fixed length identifier stored in said reception information storing means with the fixed length identifier that is output from said identifier converting means, generating the compared result of the fixed length identifiers, and identifying the contents data corresponding to the user's request using the
15 generated compared result of the fixed length identifiers.

6. The receiving apparatus as set forth in claim 5,

20 wherein when said contents data identifying means has determined that the fixed length identifier stored in said reception information storing means matches the fixed length identifier that is output from said second identifier converting means as the compared result of the fixed length identifiers, said contents
25 data identifying means compares the indefinite length identifier corresponding to the fixed length identifier stored in said reception information storing means with

the indefinite length identifier corresponding to the fixed length identifier that is output from said second identifier converting means and generates the compared result of the indefinite length identifiers, and

5 wherein when said contents data identifying means has determined that the indefinite length identifier corresponding to the fixed length identifier stored in said reception information storing means matches the indefinite length identifier corresponding to the fixed length identifier stored in said reception information storing means with the indefinite length identifier corresponding to the fixed length identifier that is output from said second identifier converting means as the determined result of the indefinite length
10 identifiers, said contents data identifying means determines that the contents data identified by the indefinite length identifier is the contents data corresponds to the user's request.

7. A transmitting and receiving system,
20 comprising:

 a transmitting apparatus having:
 transmission data storing means for storing contents data,

 identifier adding means for adding an
25 indefinite length identifier to the contents data,

 identifier converting means for converting the indefinite length identifier into a fixed length

identifier;

transmitting means for transmitting the contents data, the indefinite length identifier, and the fixed length identifier; and

5 a receiving apparatus having:

receiving means for receiving data that is transmitted,

reception information storing means for storing contents data and an indefinite length identifier contained in the data and the fixed length identifier,

inputting means for inputting a user's request for contents data,

15 identifier converting means for converting an indefinite length identifier added to the contents data corresponding to the user's request into a fixed length identifier, and

contents data identifying means for comparing the fixed length identifier stored in said reception information storing means with the fixed length identifier that is output from said identifier converting means, generating the compared result of the fixed length identifiers, and identifying the contents data corresponding to the user's request using the generated compared result of the fixed length identifiers.

25 8. A transmitting method for transmitting

contents data, comprising the steps of:

storing contents data;

adding an indefinite length identifier to the
contents data;

5 converting the indefinite length identifier
into a fixed length identifier; and

transmitting the contents data, the
indefinite length identifier, and the fixed length
identifier.

10 9. A receiving method for receiving contents
data, comprising the steps of:

receiving data that is transmitted;

storing contents data, an indefinite length
identifier, and a fixed length identifier contained in
15 the data;

converting the indefinite length identifier
contained in the data into a fixed length identifier;
inputting a user's request for contents data;
converting an indefinite length identifier
20 added to the contents data corresponding to the user's
request into a fixed length identifier;

comparing the result of the first identifier
converting step with the result of the second
identifier converting step; and

25 identifying the contents data corresponding
to the user's request using the result of the fixed
length identifier comparing step.

ABSTRACT

A URI converting portion 302 converts a URI contained in data received by a receiving portion 301 into a fixed length URI. The fixed length URI is stored to a reception information storing portion 303 along with the data received by the receiving portion 301. On the other hand, a URI of desired contents data that is input from a URI input portion 307 is converted into a fixed length URI by a URI converting portion 305. A URI comparing portion 306 compares the fixed length URI stored in the reception information storing portion 303 with an output of the URI converting portion 305. When a match is detected as the compared result, the indefinite length URIs corresponding to the fixed length URIs (namely, the URI contained in the received data and the URI that is input from the URI input portion 307) are compared. When a match is detected as the compared result, it is determined that the contents data to which the indefinite length URI is added is that contents data that the user desires.





Fig. 1**Fig. 2**

Fig. 3**Fig. 4**

```

URI_descriptor() {
    descriptor_tag
    descriptor_length
    for (i=0; i<N; i++) {
        URI_character
    }
}
  
```

Fig. 5**Fig. 6**

event_id: 100
 start_time: 21:00
 duration: 60min
 URI_descriptor: lid://www.abc.com/abc_news/night


Fig. 7


Fig. 8



Fig. 9**Fig. 10**

Fig. 11

```

URI_descriptor() {
    descriptor_tag
    descriptor_length
    for (i=0;i<N;i++) {
        URI_character
    }
    URI_hash_value

```

Fig. 12

```

event__id: 100
start__time: 21:00
duration: 60min
URI_descriptor:
    lid://www.abc.com/abc_news/night
    b2a11afc568b6df62badef691cf0b1ed

```

```

202 ...   URI ADDING PORTION
302 ...   URI CONVERTING PORTION
305 ...   URI CONVERTING PORTION
306 ...   URI COMPARING PORTION
1202 ...  URI ADDING PORTION
1204 ...  URI CONVERTING PORTION
1305 ...  URI CONVERTING PORTION
1306 ...  URI COMPARING PORTION

```

Declaration and Power of Attorney for Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

私は、以下に記名された発明者として、ここに下記の通り宣言する：

As a below names inventor, I hereby declare that:

私の住所、郵便の宛先として国籍は、私の氏名の後に記載された通りである。

My residence, post office address and citizenship are as stated next to my name:

下記の名称の発明について、特許請求範囲に記載され、且つ特許が求められている発明主題に関して、私は、最初、最先且つ唯一の発明者である（唯一の氏名が記載されている場合）か、或いは最初、最先且つ共同発明者である（複数の氏名が記載されている場合）と信じている。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled. **Transmitting Apparatus, Receiving Apparatus, Transmitting and Receiving System, Transmitting Method, and**

Receiving Method

the specification of which is attached hereto unless the following box is checked:

上記発明の明細書はここに添付されているが、下記の箱がチェックされている場合は、この限りでない：

☒ was filed on 3 March 2000
as United States Application Number of
PCT International Application Number PCT/JP00/01271
and was amended on
(if applicable).

☐ の日に出版され、
この出版の米国出願番号またはPCT国際出願番号は、
であり、且つ
の日に補正された出願（該当する場合）

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、上記の補正案によって補正された、特許請求範囲を含む上記明細書を検討し、且つ内容を理解していることをここに表明する。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

私は、連邦規則法典第37編規則1.56に定義されている、特許性について重要な情報を開示する義務があることを認める。

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the need of the individual case. Any comments on the amount of time you are required to complete this form should be sent to Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner of Patents and Trademarks, Washington, DC 20231.

日本語宣言書

私は、ここに、以下に記載した外国での特許出願または発明者証の出願、或いは米国以外の少なくとも一國を指定している米国法第35条第365条(a)によるPCT国際出願について、同第119条(a)(i)項又は第365条(a)項に基づいて優先権を主張するとともに、優先権を主張する本出願の出願日より前の出願日を有する外国での特許出願または発明者証の出願、或いはPCT国際出願については、いかなる出願も、下記の内容をチェックすることにより示した。

Prior Foreign Application(s)

外国での先行出願

11-055859

(Number)

(番号)

Japan

(Country)

(国名)

PCT/JP00/01271

(Number)

(番号)

PCT

(Country)

(国名)

(Number)

(番号)

(Country)

(国名)

(Number)

(番号)

(Country)

(国名)

(Number)

(番号)

(Country)

(国名)

(Number)

(番号)

(Country)

(国名)

私は、ここに、下記のいかなる米国仮特許出願についても、その米国法第35条第119条(a)項の利益を主張する。

(Application No.)

(出願番号)

(Filing Date)

(出願日)

私は、ここに、下記のいかなる米国出願についても、その米国法第35条第120条に基づき利益を主張し、又米国を指定するいかなるPCT国際出願についても、その同第365条(a)に基づき利益を主張する。また、本出願の各特許請求の範囲の主題が、米国法第35条第119条第1段に規定された態様で、先行する米国出願又はPCT国際出願に開示されていない場合においては、その先行出願の出願日と本国内出願日またはPCT国際出願日との間の期間中に入手された情報で、連邦規則法第37条規則1.56に定義された特許性に關する重要な情報について開示義務があることを承認する。

(Application No.)

(出願番号)

(Filing Date)

(出願日)

私は、ここに表明された私自身の知識に係わる陳述が真実であり、且つ情報を偽造することに基づく陳述が、真実であると信じられることを宣誓し、さらに、故意に虚偽の陳述などを行った場合は、米国法第18条第1001条に基づき、罰金または拘禁、若しくはその両方より懲罰され、またそのような故意による虚偽の陳述は、本出願またはそれに対して発行されるいかなる特許も、その有効性に問題が生ずることを理解した上で陳述が行われたことを、ここに宣言する。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT international application having a filing date before that of the application for which priority is claimed.

Priority Not Claimed

優先権主張なし

3 March 1999
(Day/Month/Year Filed)☐3 March 2000
(Day/Month/Year Filed)☐

(Day/Month/Year Filed)

☐

(Day/Month/Year Filed)

☐

(Day/Month/Year Filed)

☐

(Day/Month/Year Filed)

☐

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)

(出願番号)

(Filing Date)

(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(d) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

(Status: Patented, Pending, Abandoned)

(現況: 特許許可、係属中、放棄)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

日本語宣言書

委任状：私は本出願を審査する手続を行い、且つ米国特許商標庁との全ての業務を遂行するために、記名された発明者として、下記の弁護士及び/または弁護士を任命する。(氏名及び整理番号を記載すること)

書類送付先

直通電話連絡先：(氏名及び電話番号)

唯一または第一発明者氏名

発明者の署名

日付

住所

国籍

郵便の宛先

第二共同発明者がいる場合、その氏名

第二共同発明者の署名

日付

住所

国籍

郵便の宛先

(第三以下の共同発明者についても同様に記載し、署名をすること)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

WILLIAM S. FROMMER, Registration No. 25,506 and
DENNIS M. SMID, Registration No. 34,930

Send Correspondence to:

WILLIAM S. FROMMER, Esq.
c/o FROMMER LAWRENCE & HAUG LLP
745 Fifth Avenue
New York, New York 10151

Direct Telephone Calls to: (212) 588-0800

To the attention of: WILLIAM S. FROMMER

Full name of sole or first inventor

Fumihiko NISHIO

Inventor's signature

Date

Fumihiko Nishio

Sep. 29, 2000

Residence

Tokyo, Japan

Citizenship

Japan

Post Office Address:

Sony Corporation
7-35 Kitashinagawa 6-Chome
Shinagawa-Ku, Tokyo 141, Japan

Full name of second joint inventor, if any

Yoshihisa GONNO

Second Inventor's signature

Date

Yoshihisa Gonno

Sep. 29, 2000

Residence

Kanagawa, Japan

Citizenship

Japan

Post Office Address:

Sony Corporation
7-35 Kitashinagawa 6-Chome
Shinagawa-Ku, Tokyo 141, Japan

(Supply similar information and signature for third and subsequent joint inventors)

日本語宣言書

委任状: 私は本出願を審査する手続を行い、且つ米国特許商標庁との全ての業務を遂行するために、記名された発明者として、下記の弁理士及び/または弁理士を任命する。(氏名及び整理番号を記載すること)

書類送付先

直通電話連絡先: (氏名及び電話番号)

第三共同発明者がある場合、その氏名

第三共同発明者の署名

日付

住所

国籍

郵便の宛先

第四共同発明者がある場合、その氏名

第四共同発明者の署名

日付

住所

国籍

郵便の宛先

(第五以下の共同発明者についても同様に記載し、署名をすること)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

WILLIAM S. FROMMER, Registration No. 25,506 and
DENNIS M. SMID, Registration No. 34,930

Send Correspondence to:
WILLIAM S. FROMMER, Esq.
c/o FROMMER LAWRENCE & HAUG LLP
745 Fifth Avenue
New York, New York 10151

Direct Telephone Calls to: (212) 588-0800
To the attention of: **WILLIAM S. FROMMER**

Full name of third joint inventor, if any

Kazuo HARAOKA

Third inventor's signature

Date

Residence

Tokyo, Japan

Citizenship

Japan

Post Office Address:

Sony Corporation
7-35 Kitashinagawa 6-Chome
Shinagawa-Ku, Tokyo 141, Japan

Full name of fourth joint inventor, if any

Kazuhiko TAKABAYASHI

Fourth inventor's signature

Date

Residence

Tokyo, Japan

Citizenship

Japan

Post Office Address:

Sony Corporation
7-35 Kitashinagawa 6-Chome
Shinagawa-Ku, Tokyo 141, Japan

(Supply similar information and signature for fifth and subsequent joint inventors)

日本語宣言書

委任状: 私は本出願を審査する手続を行い、且つ米国特許商標庁との全ての業務を遂行するために、記名された発明者として、下記の弁護士及び/または弁理士を任命する。(氏名及び整理番号を記載すること)

書類送付先

直通電話連絡先: (氏名及び電話番号)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

WILLIAM S. FROMMER, Registration No. 25,506 and
DENNIS M. SMID, Registration No. 34,930

Send Correspondence to:
WILLIAM S. FROMMER, Esq.
c/o FROMMER LAWRENCE & HAUG LLP
745 Fifth Avenue
New York, New York 10151

Direct Telephone Calls to: (212) 588-0800
To the attention of: **WILLIAM S. FROMMER**

Full name of fifth joint inventor, if any

Yasuaki YAMAGISHI

Fifth inventor's signature

Date

Residence

Kanagawa-Japan

Citizenship

Japan

Post Office Address:

Sony Corporation
7-35 Kitashinagawa 6-Chome
Shinagawa-Ku, Tokyo 141, Japan

Full name of sixth joint inventor, if any

Sixth Inventor's signature

Date

Residence

Citizenship

Post Office Address:

Sony Corporation
7-35 Kitashinagawa 6-Chome
Shinagawa-Ku, Tokyo 141, Japan

(Supply similar information and signature for seventh and subsequent joint inventors)

第五共同発明者がある場合、その氏名

第五共同発明者の署名

日付

住所

国籍

郵便の宛先

第六共同発明者がある場合、その氏名

第六共同発明者の署名

日付

住所

国籍

郵便の宛先

(第七以下の共同発明者についても同様に記載し、署名をすること)